

PRODUCT DATA

PARACEM DECO PRESTIGE

DESCRIPTION

Water-based, extra matt paint with good hiding characteristics and washability, for interior walls and ceilings. Long open time, and therefore no visible transitions. Highly suitable for surfaces exposed to incidental or oblique light. Paracem Deco Prestige is a light insulating wall paint. It prevents the bleeding of most water-soluble stains such as nicotine and ink, for example.

SPECIFIC PROPERTIES

Long open time – no visible transitions - extra matt - hides imperfections - isolates most water-soluble stains - easily washable - good hiding characteristics - provides a low-tension matt film - excellent flow characteristics - can be used as a primer and finishing coat.

RECOMMENDED USES

As a decorative finish on interior walls and ceilings. Highly suitable for surfaces exposed to incidental or oblique light.

TECHNICAL SPECIFICATIONS

Appearance: Matt (degree of gloss 85°: approx. 2%)
Colour: White + ColourShop
Density: 1.45 - 1.51 g/cm³
Solids content: In volume: 38-40% (white)
In weight: 52 - 54% (white)

Recommended film thickness:

Wet film: ± 140 micron (consumption: 7 m²/l)
Dry film: ± 56 micron (consumption: 7 m²/l)

Flashpoint: Non-flammable

VOC content: 30 g/l max.
Ready-to-use mixture: 30 g/l max.
Category: A/a
EU limit values: 30 g/l (2010)
EN 13300: Wet abrasion resistance: Class 1

Drying times at 20°C/60% relative humidity
Tack-free: 1 hr
Recoatible: 2 hrs
Curing: ± 2 days

Efficiency

Theoretical: 7-10 m²/l per coat
Practical: Depends on several factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

SUBSTRATE TREATMENT

Suitable substrates are: plaster, cement, concrete, fibreboard, insulating hard foam boards, old paint, wallpaper, etc.

Always work on a dry and sound base surface. Paracem Deco Prestige may be directly applied over lightly porous substrates and old, cleaned paint layers if they are in good condition. Highly porous substrates and smooth plaster should first be impregnated with Pegafix.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu

PRODUCT DATA

PARACEM DECO PRESTIGE

Substrates with water-soluble constituents (nicotine stains, ink, etc.): it is necessary to apply two undiluted coats of Paracem Deco Prestige with an interval of 24 hours. This is to prevent bleeding through.

Persistent water spots or nicotine stains should be insulated with Pegaprim Isofix.

Then finish off with 1 or 2 coats of Paracem Deco Prestige, until they are fully hidden.

INSTRUCTIONS FOR USE

The product should be thoroughly stirred before use, to ensure homogeneity. Please conform to the efficiency in order to obtain optimal hiding.

DILUTION AND APPLICATION

Brush: Use undiluted.

Roller: Use undiluted.

Air spray: If necessary, dilute with water.

Airless spray: Nozzle: 011-013/Pressure: 180 bar
If necessary, dilute with a little water.

Cleaning up: Water.

APPLICATION CONDITIONS

> 5°C and < 80% R.H.

SAFETY

Refer to the Product Data Sheet and the information on the packaging.

SHELF LIFE

2 years from manufacturing date, if stored in the unopened, original packaging in dry, well-ventilated areas, not in direct sunlight, and at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu