

PRODUCT DATA

PEGAMAT RL ISOLE

DESCRIPTION

Deodorised low tension solvent-based insulating or blocking paint based on plastified acrylic resins.

MAIN PROPERTIES

Primer and topcoat in one - high covering power - non yellowing - low tension film - unsaponifiable - matt film without laps - covers nicotine stains, old damp spots, smoke and soot stains and numerous colorants - also suitable for insulating hard foam boards, even those in polystyrene.

RECOMMENDED USES

Low tension renovation paint for interior walls and ceilings.

TECHNICAL DATA

Appearance:	Matt (gloss 60°: < 2%)
Colour:	White
Density:	1,33 - 1,37 g/cm ³
Solids Content:	In volume: 38 - 40% In weight: 64 - 66%
Recommended film thickness:	Wet film: ± 100 micron (cons.: 10 m ² /l) Dry film: ± 40 micron (cons.: 10 m ² /l)
Flashpoint:	62°C
VOC-content:	455 g/l max.
Ready-for-use mixture:	485 g/l max.
Category:	A/i
EU Limit values:	600 g/l (2007) / 500 g/l (2010)

Drying times	20°C/50% r.h.
To touch:	3 hours
To recoat:	Wet in wet or after 4 hours
Full hardness:	± 1 day

Coverage

Theoretical:	9 - 12 m ² /l per coat
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Suitable substrates are: plaster, cement, concrete, fibreboard, insulating hard foam boards, old paints, wallpaper, etc. Substrates should be sufficiently dry and stable. Apply 1 or 2 coats according to the condition of the substrate; if necessary, the second coat can be applied wet in wet. Do not apply on Elastofill; when using Pegaflex, it must first be insulated with Porisol. Old cleaned layers in good condition and light porous substrates may be recoated directly with Pegamat RL Isole. Very porous substrates are to be impregnated first with Pegafix. Persistent stains are to be treated with Pegaprim® Isofix.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu

PRODUCT DATA

PEGAMAT RL ISOLE

APPLICATION & THINNING

- Brush: Dilute with 3-5% Thinner RL or White spirit if necessary.
- Roller: Dilute with 3-5% Thinner RL or White spirit if necessary.
- Air-atomised spray: Possible.
- Airless spray: Nozzle: 011 - 015 / Pressure: 180 bars
Dilute max. 5% with Thinner RL or White spirit if necessary.
- Cleanup: White spirit.

APPLICATION CONDITIONS

Apply in a dry and well-ventilated area.

REMARKS

White spirit increases the odour and makes its use impossible on polystyrene foam. Pegamat RL Isole is a reversible paint system, this means that it dissolves in its own solvent. Therefore, dried spots of Pegamat RL Isole can be removed with Thinner RL or white spirit. Do not tint with universal pigments or on the tinting machine.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu