

## PRODUCT DATA

## PEGAMAT AQUA ISOLE

### DESCRIPTION

Water based low tension matt renovation and stain blocking paint for use on interior walls and ceilings based on modified alkyd resins.

### MAIN PROPERTIES

Low tension film - primer and topcoat in one - insulates nicotine and smoke stains, old damp spots and numerous colorants - low odour - uniform mat white finish - long open time - high covering power.

### RECOMMENDED USES

Low tension renovation paint for interior walls and ceilings.

### TECHNICAL DATA

Appearance:	Matt (gloss 85°: 2%)
Colour:	White + base P for pastel shades
Density:	1,45 - 1,51 g/cm <sup>3</sup>
Solids Content:	In volume: 38 - 42% (white) In weight: 58 - 62% (white)
Recommended film thickness:	Wet film: ± 140 micron (consumption: 7 m <sup>2</sup> /l) Dry film: ± 56 micron (consumption: 7 m <sup>2</sup> /l)
Flashpoint:	Not flammable
VOC-content:	53 g/l max.
Ready-for-use mixture:	53 g/l max.
Category:	A/i
EU Limit values:	140 g/l (2007) / 140 g/l (2010)

### Drying times 20°C/50% r.h.

To touch:	1 hour
To recoat:	2 hours
Full hardness:	± 2 days

### Coverage

Theoretical:	7 m <sup>2</sup> /l per coat
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

Suitable substrates are: plaster, cement, concrete, fibreboard, insulating hard foam boards, old paints, wallpaper, etc.

Apply on a dry and sound substrate. Apply 1 or 2 coats according to the condition of the substrate.

Old cleaned layers in good condition and light porous substrates may be recoated directly with Pegamat Aqua Isole.

On very absorbent substrates (not painted), apply an impregnation coat of Pegafix.

On substrates with nicotine spots: first clean these with an ammonia solution in order to receive a better efficiency of the paint.

Can be applied on completely dry Elastofill/Pegaflex without the risk of crack formation.

### DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

#### Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

#### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum UK Ltd.

Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

## PRODUCT DATA

## PEGAMAT AQUA ISOLE

### APPLICATION & THINNING

Brush:	Apply undiluted.
Roller:	Apply undiluted.
Air-atomised spray:	If necessary, dilute with a little water.
Airless spray:	Nozzle: 011 - 013 / Pressure: 180 bar If necessary, dilute with a little water.
Cleanup:	Water.

### APPLICATION CONDITIONS

> 5°C and < 80% R.H.

### REMARKS

- Apply a preliminary test patch in case of old damp spots and colour marks. When insulation properties are insufficient, use Pegamat RL Isole or Pegaprim Isofix.
- Can be applied directly on Pegamat RL Isole, Pegaprim Isofix and Pegaprim Xpress.
- Can be recoated with all water-based paint, and also with Pegamat RL Isole.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

#### Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

#### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum UK Ltd.

Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)