

PRODUCT DATA

PARACEM DECO NATURE NF PRIMER

DESCRIPTION

Waterborne acrylic paint for high-quality indoor works.

MAIN PROPERTIES

Very good fixating characteristics.

RECOMMENDED USES

Applicable on most substrates (plaster, bricks, concrete, etc.) in residential and public buildings.

TECHNICAL DATA

Appearance:	Matt
Colour:	White + Mathymix / ColourShop
Density:	$\pm 1.28 - 1,3 \text{ g/cm}^3$
Solids Content:	In volume: $44 \pm 2\%$ In weight: $54 \pm 2\%$
Flashpoint:	Not flammable
VOC-content:	Max. 3 g/l (tinted max 15 g/l)

Drying times 20°C/60% RH

To touch: Appr. 1 hour

To recoat: Appr. 8 hours

Coverage

Theoretical: 8 - 10 m²/l

Practical: Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

SURFACE PREPARATION

The surface should be dry and clean, free of dirt and dust. Remove loose paint.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION & THINNING

Brush: Apply undiluted.

Roller: Apply undiluted.

Air-atomised spray: If required dilute with maximum 3% water.

Airless spray: Nozzle: 9 - 11 / Pressure: 200 bars, dilute with maximum 3% water.

Cleanup: Water.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

PRODUCT DATA

PARACEM DECO NATURE NF PRIMER

APPLICATION CONDITIONS

Dry weather, min. 10°C

REMARK

When the product is tinted the Ecolabel does not apply anymore.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 10° and 35°C.

Minimise paint wastage by estimating how much paint you will need.

Recover unused paint for re-use.

Reuse of paint can effectively minimise the products' life cycle environmental impact.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com