

PRODUCT DATA

PARACEM DECO NATURE NF MATT

DESCRIPTION

Waterborne acrylic paint for high-quality indoor works. The paint has very low VOC levels. The white version has the Ecolabel.

MAIN PROPERTIES

Excellent flow - smooth matt aspect - high covering power – tendency not to overlap.

RECOMMENDED USES

Decorative and matt finishing for indoor walls and ceilings.
Applicable on most substrates (plaster, bricks, concrete, etc.) in residential and public buildings. Applicable in 2 coats.

PRIMER

Paracem Deco Nature Matt can be applied directly on previously painted surfaces in good condition and on non-porous substrates.

Very porous substrates, water-resistant plasterboard and smooth plaster need to be sealed first with Paracem Deco Nature Primer.

TECHNICAL DATA

Appearance:	Matt
Colour:	White + Mathymix / ColourShop
Density:	± 1,49
Solids Content:	In volume: 43 ± 2% In weight: 60 ± 2%
Flashpoint:	Not flammable
VOC-content:	Max. 9,45 g/l (tinted max 15 g/l)
Loi Grenelle classification:	A+
EN 13300:	Wet scrub resistance: Class 1 (white), Class 2 (Mathymix/Colourshop)

Drying times	20°C/60% RH
To touch:	1 hour
To recoat:	6-8 hours

Coverage

Theoretical:	8 - 10 m ² /l per coat, 2 coats recommended
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

The surface should be dry and clean.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION & THINNING

Brush:	Apply undiluted.
Roller:	Apply undiluted.
Air-atomised spray:	If necessary dilute with maximum 3% water.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu

PRODUCT DATA

PARACEM DECO NATURE NF MATT

Airless spray: Nozzle: 009 - 011 / Pressure: 200 bars, dilute with maximum 3% water.

Cleanup: Water.

APPLICATION CONDITIONS

Dry and clean substrates, min. 5°C

REMARK

When the product is tinted the Ecolabel does not apply anymore. (Adding colorants increases the VOC level).

SAFETY

For prolonged or repeated handling, use nitrile rubber gloves. If workers are exposed to concentrations above the exposure limit, they must use respirators. Recommended: organic vapour (Type A) and particulate filter (EN 141)

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 10° and 35°C.

Minimise paint wastage by estimating how much paint you will need.

Recover unused paint for re-use.

Reuse of paint can effectively minimise the products' life cycle environmental impact.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu