

PRODUCT DATA

PARACEM DECO NATURE NF SATIN

DESCRIPTION

Waterborne acrylic paint for high-quality indoor works.

MAIN PROPERTIES

Excellent flow – good mechanical resistance against rubbing - smooth satin aspect – closed coating structure – washable - high covering power – tendency not to overlap.

RECOMMENDED USES

Decorative finishing for indoor walls and ceilings.

Applicable on most substrates (plaster, bricks, concrete, etc.) in residential and public buildings.

TECHNICAL DATA

Appearance: Satin
Colour: White + Mathymix / ColourShop
Density: $\pm 1,36$
Solids Content: In volume: $44 \pm 2\%$
In weight: $59 \pm 2\%$
Flashpoint: Not flammable
VOC-content: Max. 0,5 g/l
EN 13300: Wet scrub resistance: Class 1

Drying times 20°C/60% RH

To touch: 1 hour

To recoat: 6-8 hours

Coverage

Theoretical: 10-12 m²/l per coat, 2 coats recommended

Practical: Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

SURFACE PREPARATION

Old cleaned layers in good condition and light porous substrates may be recoated directly with Paracem Deco Nature. Very porous substrates, smooth plaster and water-resistant plasterboard are to be impregnated first with Paracem Deco Nature Primer.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION & THINNING

Brush: Apply undiluted

Roller: Apply undiluted.

Air-atomised spray: If necessary dilute with maximum 3% water.

Airless spray: Nozzle: 9-11 / Pressure: 200 bars, dilute with maximum 3% water.

Cleanup: Water.

APPLICATION CONDITIONS

Dry and clean substrates, min. 10°C

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu

PRODUCT DATA

PARACEM DECO NATURE NF SATIN

REMARK

When the product is tinted the Ecolabel does not apply anymore.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Minimise paint wastage by estimating how much paint you will need.

Recover unused paint for re-use.

Reuse of paint can effectively minimise the products' life cycle environmental impact.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu